



SAFETY DATA SHEET

Microlac Sheen Finish

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME Microlac Sheen Finish
 PRODUCT NO. 0027 line
 SUPPLIER Dacrylate Paints Ltd,
 Lime Street,
 Kirkby-in-Ashfield
 Nottingham NG17 8AL
 01623-753845

2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
COBALT CARBOXYLATE		13586-82-8	< 1%	Xi;R38. R43.
DE-AROMATISED KEROSENE	265-150-3	64742-48-9	< 1%	Xn;R65.
ETHYL METHYL KETOXIME	202-496-6	96-29-7	< 1%	Carc3;R40 Xn;R21 R43 Xi;R41
WHITE SPIRIT	265-191-7	64742-88-7	10-30%	Xn;R65. N;R51/53. R10.

The Full Text for all R-Phrases are Displayed in Section 16

3 HAZARDS IDENTIFICATION

Flammable. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION N;R51/53. R10.

4 FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Provide rest, warmth and fresh air. Get medical attention if any discomfort continues.

INGESTION

Get medical attention immediately! Rinse mouth thoroughly. Provide rest, warmth and fresh air. DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS!

SKIN CONTACT

Remove affected person from source of contamination. Get medical attention if any discomfort continues.

EYE CONTACT

Remove victim immediately from source of exposure. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Fire can be extinguished using: Carbon dioxide (CO2). Alcohol resistant foam. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

UNUSUAL FIRE & EXPLOSION HAZARDS

May develop highly toxic or corrosive fumes if heated. Vapours are heavier than air and may spread near ground to sources of ignition.

6 ACCIDENTAL RELEASE MEASURES

SPILL CLEAN UP METHODS

Clean-up personnel should use respiratory and/or liquid contact protection. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate.

7 HANDLING AND STORAGE

Microlac Sheen Finish

USAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. The accumulation of contaminated rags and of dry overspray, particularly in spray booth filters, may result in spontaneous combustion. Good housekeeping standards, regular safe removal of waste materials and regular maintenance of spray booth filters will minimise the risks of spontaneous combustion and other fire hazards.

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry and cool place.

STORAGE CLASS

Flammable liquid storage.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

INGREDIENT COMMENTS

OES = Occupational Exposure Standard.

PROTECTIVE EQUIPMENT



RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Workplace Exposure Limit.

HAND PROTECTION

Use protective gloves made of: Polyvinyl alcohol (PVA). Viton rubber (fluor rubber).

HYGIENE MEASURES

Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke. **DO NOT SMOKE IN WORK AREA!**

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid
COLOUR	Varying
ODOUR	Characteristic
SOLUBILITY	Insoluble in water

10 STABILITY AND REACTIVITY

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition.

MATERIALS TO AVOID

Strong oxidising substances. Strong acids. Strong alkalis.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO₂).

11 TOXICOLOGICAL INFORMATION

ROUTE OF ENTRY

Inhalation. Ingestion.

12 ECOLOGICAL INFORMATION

BIOACCUMULATION

Not known.

DEGRADABILITY

Not known.

13 DISPOSAL CONSIDERATIONS

Microlac Sheen Finish

DISPOSAL METHODS

Recover and reclaim or recycle, if practical. Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION



PROPER SHIPPING NAME	PAINT or PAINT RELATED MATERIAL		
UN NO. ROAD	1263	ADR CLASS NO.	3
ADR CLASS	Class 3: Flammable liquids.	ADR PACK GROUP	31(c)
HAZARD No. (ADR)	30	ADR LABEL NO.	3
HAZCHEM CODE	3[Y]	CEFIC TEC(R) NO.	30G80
RID CLASS NO.	3	RID PACK GROUP	31(c)
UN NO. SEA	1263	IMDG CLASS	3.3
IMDG PAGE NO.	3372	IMDG PACK GR.	III
EMS	3-05	MFAG	310 or 313
MARINE POLLUTANT	No.	UN NO. AIR	1263
AIR CLASS	3	AIR PACK GR.	III

15 REGULATORY INFORMATION

LABELLING



Dangerous for the environment

RISK PHRASES

R10	Flammable.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SAFETY PHRASES

S24/25	Avoid contact with skin and eyes.
S36/37/39	Wear suitable protective clothing, gloves and eye/face protection.
S51	Use only in well-ventilated areas.
S57	Use appropriate containment to avoid environmental contamination.
S60	This material and its container must be disposed of as hazardous waste.
S61	Avoid release to the environment. Refer to special instructions/safety data sheets.
P14	Contains COBALT CARBOXYLATE,ETHYL METHYL KETOXIME. May produce an allergic reaction.

UK REGULATORY REFERENCES

Petroleum (Consolidation) Act, as amended 1984 SI 1244. Highly Flammable Liquid Regulations 1972.

ENVIRONMENTAL LISTING

Rivers (Prevention of Pollution) Act 1961. Control of Pollution (Special Waste Regulations) Act 1980.

EU DIRECTIVES

System of specific information relating to Dangerous Preparations. 2001/58/EC.

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

16 OTHER INFORMATION

Microlac Sheen Finish

GENERAL INFORMATION

Revised in accordance with CHIP 3

INFORMATION SOURCES

Dangerous Properties of Industrial Materials Report, N.Sax et.al.

REVISION COMMENTS

New Issue supersedes all SDS prior to January 2006

REVISION DATE May 2007

REV. NO./REPL. SDS GENERATED NEW

SDS NO. 10792

RISK PHRASES IN FULL

R10	Flammable.
R21	Harmful in contact with skin.
R38	Irritating to skin.
R40	Limited evidence of a carcinogenic effect.
R41	Risk of serious damage to eyes.
R43	May cause sensitisation by skin contact.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.