

CONSERVATORY INTERIORS BY VALE

PRODUCT INFORMATION

Product Name:	WOOD FINISH SEMI GLOSS
Reference Number:	27-line
Coating Type:	Microporous Finish for timber based on light-fast, lead-free pigments.
Typical Uses:	Microporous Finish for use over Microlac primer/undercoat. Microporosity allows moisture-vapour to pass through the paint film reducing the tendency for wet rot, etc., and failure due to blistering, cracking.
Colours Available:	The Vale Garden range of 24 colours.
Appearance of Dried Film:	45-50% Gloss
Theoretical Coverage:	Approximately 10m ² per litre depending on film thickness applied and porosity of substrate.
Drying Time at 20^oC:	Touch Dry: 4 Hours
(Will vary with temperature, air movement etc.)	Firm Dry: 8 Hours
	Overcoat: Overnight
Packaging:	Sample Tin, 1 litre, 2.5 litre and 5 litre containers.
Shelf Life:	2 years in unopened containers, when stored under cover in good storage conditions.
Storage:	Under cover within temperature range of 5 ^o C to 32 ^o C.
Surface Preparation:	All new woodwork should be clean and dry with moisture content of less than 20% and primed using Microlac Primer/undercoat ref: 27-60. If the woodwork has been previously painted, it is advised that all the old paint be removed to leave a clean substrate. If the old coatings are not removed the Microporous nature of the system will be ineffective.
Application:	Applied by brush.
Clean Up:	Thinner R1.
Health and Safety:	Please see relevant MSDS sheet.

Data sheets are issued to supply **general information** on the product but without warranty. Since conditions of service and application are beyond our control we cannot accept claims for loss, damage etc., based on this information. Vale Garden Houses will not accept any claim for consequential or incidental damages.